

## Crush Tester Accessory

### Corrugated fiberboard Edge Crush Test/adhesive sample cutter

#### Technical data:

- 1, Sample size: 25mm×100mm (ECT), 25mm×80mm (adhesive)
- 2, Result error: ±0.5mm
- 3, Maximum length: 220mm
- 4, Maximum thickness: 18mm
- 5, Dimension (l×w×h): 430mm×380mm×200mm
- 6, weight: 22kg



### Edge Crush Test metal block

It is two blocks to fixate the specimen

Size: 10×2×2(cm)

Weight: 0.2kg



### Corrugated fiberboard Flat Crush Test

#### Technical data:

- 1, Sample area: (two types) : 64.5cm<sup>2</sup> 32.2cm<sup>2</sup>
- 2, Result error: ±0.5cm<sup>2</sup>
- 3, Sample thickness: ≤7mm
- 4, weight: 2.5kg



### Ring Crush Test sample cutter

#### Technical data:

- 1, Sample length: 152 mm;  
Sample width: 12.7 mm;  
Two length sides parallelism: <0.015mm
- 2, Sample thickness: (0.1~1.0)mm
- 3, Dimension (l×w×h): 570×190×368(mm)
- 4, weight: 19.5kg



### RCT central set

#### Technical data:

1. Ring groove width: 0.15mm ~ 1.00mm, 13 kinds of specifications
2. Dimensions (l × w × h): 440 × 190 × 48 mm
3. Weight: 2 kg



### Corrugated fiberboard Pin Adhesive Strength Test clamp (PAT)

#### Technical data:

- 1, Needle diameter: φ3mm (A flute), φ2mm (B, C flute) φ1mm (E flute)
- 2, Result error: assembled <1/100; pressed (300N) <1/200
- 3, Maximum dimension (l×w×h): 100×50×45(mm)
- 4, weight: 0.6kg

