

## SKZ1056 Salt Spray Test Chamber



Suitable for all kinds of electrical materials and parts into the salt spray corrosion testing. The disposable molded fiberglass shell, transparent cover. High-precision digital meters, PID fuzzy control. Pt100 test sensors, dual pressure protection and over-temperature protection. Air-spray, spray and adjustable time interval can be set. Temperature fluctuation  $\leq \pm 0.5$  °C, temperature uniformity  $\leq \pm 2$  °C. Salt settlement: 1 ~ 2ml/80cm<sup>2</sup> hours, special nozzles, no crystallization phenomena.

**Standard:**

IEC60068-2-40, IEC 60068-3-5, IEC68-2-11, ISO7253, ISO 9227, GB10587, GB/T2423.17, GB/T5170.8, GJB150.11-86

**Technical parameters:**

Type	SKZ105 6A	SKZ1056 B	SKZ1056 C	SKZ1056D	SKZ1056 E	SKZ1056 F
Working size inner (mm)	500×630 ×450	550×900× 600	750×1100 ×600	1000×1300 ×600	850×1600 ×900	1000×200 0×800
Dimension (mm)	680×122 0×1100	900×1640 ×1315	1010×174 0×1315	1290×2060 ×1495	1300×237 0×1633	1450×277 0×1830
Structure	Vertical single chamber	Headpiece			Cover (transparent cover / fiberglass cover)	
		Under-part			Workroom	
Technical parameter	Temperature Range	35°C			Neutral salt spray test	
		55°C			CASS salt spray test	
	Temperature fluctuations	$\leq \pm 0.5$ °C				

	Temperature uniformity	$\leq 2^\circ\text{C}$			
	Salt settlement	1~2ml/80cm <sup>2</sup> hour			
	Spray	Tower air flow spray	Continuous		
			Intermittently		
	Time Set	Spray time			
		Interval time			
Material	inner and shell casing is made of fiberglass molded integrally molded, corrosion-resistant, shock-resistant cleaning, no leakage				
configuration	Controller	Japanese RKC-CD701 or Fuji			
	Heater	Heating cabinet	Heating wire		
		Saturated steam heating	Stainless steel heating pipe		
		PVC sample holder 2 layers			
		20L salt water tank			
	10L distilled water tank				
Accessory	Power outlet: 1pc				
	Fuse: 3pcs				
	Switch button: 2pcs				
	Sensor: 1pc				
Security	Leakage protection				
	South Korea, "rainbow" over-temperature alarm protection				
	Fast Fuse				
	Pressure protection	Inlet pressure protection			
		Spray pressure protection			
	Line fuse, all sheathed terminal				
Power	220V/3Kw/4Kw				